



SKY WHITE 99 XC

Sky White 99 XC films effectively eliminate solar heat and glare. Its mirror aspect and totally blackout guarantees privacy from prying eyes and provides a "visual" protection day and night.



TECHNICAL DATASHEET

Data calculated based on film applied to clear glass 3 mm thick (*on double glazing 4-16-4)

Ultraviolet transmission	1 %
Visible light transmission	<1~%
Reflection of external visible light	88 %
Reflection of internal visible light	11 %
Total solar energy rejected	99 %
Total solar energy rejected 2*	99 %
Solar ratio :	
Solar energy reflection	85 %
Solar energy absorption	14 %
Solar energy transmission	1 %
Reduction in Solar Glare	100 %
g-value	0.03
u-value	5.1
Shading coefficient	0.2
Installation type : External application	
Roll length	30.5 m
PET / PVC composition	PET
Thickness	100 μ
Colour : SILVER	


INSTALLATION ADVICE

Vertical installation and on standard glass surface**

Clear single pane	\checkmark
Tinted single pane	
Reflective tinted single pane	~
Clear double pane	~
Tinted double pane	~
Reflective tinted double pane	
Gas-filled double pane - Low E	~
STADIP EXT. clear double pane	~
STADIP INT. clear double pane	~

✓ Yes Caution × Not recommended

*Recommendations provided on the basis of a glazed surface covering up to 2.5m², contact us for definitive details or to obtain a thermal chock analysis report.



MAINTENANCE INSTRUCTIONS

Soapy water solution (ref. 0805 Film on), do not clean for at least a month and do not apply any type of sticker or adhesive on the film.

Non-contractual data, SOLAR SCREEN® reserves the right to modify the composition of its films at any time. Consult our guarantee vouchers and our general conditions of sale.

SOLAR SCREEN® EUROPEAN SALES CENTER 18 Rue du Commerce L-3895 FOETZ TEL : +352 26 00 84 82 WWW.SOLARSCREEN.EU